

# **KEY 9000 MMA HARDENER**

#### DESCRIPTION

**KEY 9000 MMA HARDENER** is a white dry powder consisting of 50% BPO, Dibenzoyl Peroxide. It must be well mixed with Key Resin MMA resins before adding other fillers and aggregates to ensure the hardening of the mixed materials. Any exceptions to this mixing sequence must be confirmed with Key Resin Technical Services.

**KEY 9000 MMA HARDENER** is soluble in Acrylic (MMA) resin. After mixing the powder into reactive acrylic it starts the polymerization reaction, which leads to the hardening process of the floor system.

## **TECHNICAL DATA**

Appearance	Sandy, white dry powder
Content of Dibenzoyl Peroxide and Dicyclohexyl Phthalate	Approximately 50%
Self-Accelerating Decomposition	140°F
Temperature (SADT)	
Self-Ignition Temperature	>680°F
Solubility	Not soluble in water

## **PACKAGING**

8 vol. oz.	8 vol. oz. jar
5 lbs.	1 gallon pail
15 lbs.	3 gallon pail
55 lbs.	1 box

## **PROCESSING**

**KEY 9000 MMA HARDENER** must only be mixed immediately before the application of Key Resin MMA resins. Fillers and aggregates are added <u>after</u> the hardener is added and mixed, unless otherwise approved by Key Resin Technical Service. It is important to follow the mix ratio chart for each resin pertaining to temperature and desired set time, refer to the individual resin product data sheets and the Key 9000 MMA Hardener Mixing Chart document for the correct amount of hardener. The amount of hardener needed depends on the type of resin being used and the temperature.

#### SAFETY NOTES

**KEY 9000 MMA HARDENER** is an oxidizing agent that violently decomposes under the influence of heat or when in contact with reducing agents. <u>Do Not Mix With Accelerators.</u> Store separately from the Key Resin MMA resins. Review MSDS information thoroughly.

#### **STORAGE**

Store in tight containers in dry environments below 80°F.

## WARRANTY

Information regarding Key Resin brand MMA resins and systems is based upon extensive research and experience in the field of applied engineering by the manufacturer **Plasti-Chemie GMBH International.** By making such information available, Key Resin does not thereby assume any liability beyond express terms of our standard limited material warranty. Key Resin does not warrant the accuracy or completeness of any such information, whether conveyed orally or in writing, but to the best of our knowledge believe it to be accurate. We reserve the right at any time and without notice to update or improve our products and process and our information concerning the same. By Key Resin making this information available does not relieve the purchaser or user from his obligation to verify the suitability of our products and processes for the intended use or application. The purchaser and user likewise have the responsibility to ensure that the purchase, use or application does not infringe upon patent rights or other rights of third parties.

Key Resin Company ("Key") warrants for a period of one (1) year that its products will be free of manufacturing defects and will be in conformity with published specifications when handled, stored, mixed, and applied in accordance with recommendations of Key. If any product fails to meet this warranty, the liability of Key will be limited to replacement of any non-conforming material if notice of such non-conformity is given to Key within one (1) year of delivery of materials. Key may in its discretion refund the price received by Key in lieu of replacing the material. No customer, distributor, or representative of Key is authorized to change or modify the published specifications of this warranty in any way. No one is authorized to make oral warranties on behalf of Key. In order to obtain replacement or refund the customer must provide written notice containing full details of the non-conformity. Key reserves the right to inspect the non-conforming material prior to replacement. EXCEPT FOR THE EXPRESSED WARRANTY STATED ABOVE, THERE ARE NO OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR PURPOSE. KEY'S OBLIGATION SHALL NOT EXTEND BEYOND THE OBLIGATIONS EXPRESSLY UNDERTAKEN ABOVE AND KEY SHALL HAVE NO LIABILITY OR RESPONSIBILITY TO THE PURCHASER OR ANY THIRD PARTY FOR ANY LOSS, COST, EXPENSE, DAMAGE OR LIABILITY, WHETHER DIRECT OR INDIRECT, OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.