

## **KEY RESIN #401 URETHANE TOPCOAT**

#### **DESCRIPTION**

**KEY RESIN #401** is a single component aliphatic urethane topcoat used to seal **KEY LASTIC SWS**. Exhibiting excellent resistance to ultraviolet degradation, **KEY RESIN #401** provides a high-build, chemically resistant finish.

#### **KEY ADVANTAGES**

- · Resistant to UV degradation
- · Weather resistant seal coat for exterior decking systems
- · Oil, grease, and chemical resistant
- · Single component

## **KEY CONSIDERATIONS**

- Temperature and humidity sensitive cure
- Adequate ventilation and proper respirators are necessary when applied in close quarters
- Minimum application temperature of 50°F
- · Interior slab on grade installation must include a vapor barrier

#### **COMPOSITION & COLOR**

**KEY RESIN #401** is a single component, aliphatic polyurethane elastomer available in gray only. If other colors are required substitute Key #420 Aliphatic Urethane.

#### **APPLICATION**

#### SURFACE PREPARATION

Concrete surface must be in sound condition and properly prepared per manufacturer's recommendations. Refer to **Technical Bulletin #1** for surface preparation guidelines.

## **INSTALLATION**

Apply with a brush or roller. Allow to cure before applying a second coat.

#### **TECHNICAL DATA**

# Viscosity 1500±300 cps Solids Content 80% VOC 222 g/liter Weight 8.8 lbs/gallon Coverage 100 ft²/gallon yields 12.8 mils DFT

60 minutes

# **DRY TIMES @ 75°F, 50% RH**

Recoat	12 hours
Light Traffic	24 hours
Vehicular Traffic	36 hours

#### **TECHNICAL DATA**

Pot Life (77 degrees F)

#### PERFORMANCE PROPERTIES

Peel Adhesion		
1 con / tancolon	<b>ASTM C-794</b>	50 pli
Abrasion Resistance		
	ASTM-C-501	.010g loss (CS-17 wheel, 1 kg load, 1000 cycles)
Hardness, Shore A		85±5
	ASTM D-2240	8010
Tensile Strength		2000 noi
	<b>ASTM D-412</b>	2800 psi
Elongation		100%
	<b>ASTM D-412</b>	100%
Tear Resistance		150 pli
	<b>ASTM D-1004</b>	150 pli
Chemical Resistance		No Effect – motor oil, road salt, caustic, anti-freeze, gasoline.
Weather Resistance		N. V   F   O. 0.000
	<b>ASTM D-822</b>	No Visual Effect @ 2,000 hours
Permeability		4.0 Dames
	<b>ASTM E-398</b>	1.6 Perms
Fire Resistance of System		Class A an asperate
ASTM E-108/UL 790 (or equal)		Class A on concrete

## **AVAILABILITY**

**Key Resin** materials are available throughout the United States, Canada, and a number of other countries. Contact the **KEY REPRESENTATIVE** in your area for details or call Key Resin at (888)943-4532.

#### **TECHNICAL SERVICE**

**Key Resin Company** and **KRC Associates, Inc.** provide services and consultations on material selection, specification, troubleshooting, and other information on the proper repair and protection of concrete surfaces. Contact the **KEY REPRESENTATIVE** in your area for details or call Key Resin at (888)943-4532.

#### WARRANTY

Key Resin Company ("Key") warrants for a period of one (1) year that its products will be free of manufacturing defects and will be in conformity with published specifications when handled, stored, mixed, and applied in accordance with recommendations of Key. If any product fails to meet this warranty, the liability of Key will be limited to replacement of any non-conforming material if notice of such non-conformity is given to Key within (1) one year of delivery of materials. Key may in its discretion refund the price received by Key in lieu of replacing the material. No customer, distributor, or representative of Key is authorized to change or modify the published specifications of this warranty in any way. No one is authorized to make oral warranties on behalf of Key. In order to obtain replacement or refund the customer must provide written notice containing full details of the non-conforming material prior to replacement. EXCEPT FOR THE EXPRESSED WARRANTY STATED ABOVE, THERE ARE NO OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR PURPOSE. KEY'S OBLIGATION SHALL NOT EXTEND BEYOND THE OBLIGATIONS EXPRESSLY UNDERTAKEN ABOVE AND KEY SHALL HAVE NO LIABILITY OR RESPONSIBILITY TO THE PURCHASER OR ANY THIRD PARTY FOR ANY LOSS, COST, EXPENSE, DAMAGE OR LIABILITY, WHETHER DIRECT OR INDIRECT, OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.