

MATERIAL SAFETY DATA SHEET
KEY #554 EPOXY BLOCK FILLER PART B

PRODUCT NAME KEY #554 POLYAMIDE EPOXY PART B
PRODUCT CODE:

HMIS CODES: H F R P
3 3 0 --

SECTION 1: MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: KEY RESIN COMPANY
ADDRESS: 4061 Clough Woods Drive
Batavia, OH 45103
EMERGENCY NUMBER: 1-800-424-9300
INFORMATION NUMBER: 1-513-943-4225
DATE PRINTED: 07/10/03
NAME OF PREPARER: R. CAIN

SECTION 2: HAZARDOUS INGREDIENTS/SARA III INFORMATION

HAZARDOUS COMPONENTS	CAS NUMBER	OSHA PEL	ACGIH TLV	WT %	VAPOR PRESS.
*Xylene	1330-20-7	100 ppm	100 ppm	4-8	5.1 Hg @ 68 deg. F
Polyamide Resins	6841-0-231	NE	NE	14-20	NE
Glycol Ether PM Acetate	108-65-6	NE	NE	2-5	<1 Hg @ 68 deg. F
Aromatic Petroleum Distillates	64742-95-6	100 ppm	NE	13-17	3 Hg @ 68 deg. F

Substances listed are present in concentration of 1% or greater, or 0.1% if cited as a potential Carcinogen in the OSHA hazards communication standard. Where proprietary ingredient is listed, the identity is provided in 29 CFR 1910.1200.

*Indicates toxic chemical(s) subject to reporting requirements of Section 313 of Title III and of 40 CFR 372.

NE - Not Established

SECTION 3: PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE	280° F
VAPOR DENSITY	Heavier than Air
PERCENT VOLATILE BY VOLUME	42
VOC	
WEIGHT PER GALLON (lbs)	12.5 ± .25
APPEARANCE AND ODOR	Amber liquid with solvent-amine odor
SPECIFIC GRAVITY (H2O=1)	
EVAPORATION RATE	Slower than Ether

SECTION 4: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 80° F

METHOD USED:

FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: 1.0
UPPER:

EXTINGUISHING MEDIA: Foam, alcohol foam, CO2, Dry Chemical

OSHA FLAMMABILITY CLASSIFICATION: Flammable Liquid IC

SPECIAL FIRE FIGHTING PROCEDURES: Wear a NIOSH/MSHA approved self contained breathing apparatus and full protective clothing. Use water to keep fire exposed containers cool. Water may be ineffective as an extinguishing agent.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors are heavier than air and may travel along the ground or be moved ventilation to ignition sources at locations distant from material handling point. Pressure may build up in containers and create an explosion hazard.

SECTION 5: REACTIVITY DATA

STABILITY: Product stable

CONDITIONS TO AVOID: All sources of ignition

INCOMPATIBILITY (MATERIALS TO AVOID): Oxidizing agents, strong acids and bases.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Carbon monoxide, carbon dioxide, nitrogen oxides and organic compounds.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 6: HEALTH HAZARD DATA

HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

INHALATION: Headache, dizziness, uncoordination, nausea, loss of consciousness.

SKIN: Moderate irritation or defatting of skin upon prolonged or repeated contact.

EYE: Irritation, burning, tearing and redness.

INGESTION: Abdominal pain, nausea, vomiting, and diarrhea.

HEALTH HAZARDS (ACUTE AND CHRONIC):

CARCINOGENICITY: NTP CARCINOGEN: NO IARC MONOGRAPHS: NO OSHA REGULATED: NO

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

EMERGENCY AND FIRST AID PROCEDURES:

EYES: Flush with water for 15 minutes.

SKIN: Remove contaminated clothing, wash skin with soap and water.

INGESTION: Do not induce vomiting. Get medical treatment immediately.

INHALATION: Move to fresh air, aid breathing if necessary.

SECTION 7: PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Dike spill area. Absorb spill with inert absorbent material. Place in sealed metal containers for proper disposal.

WASTE DISPOSAL METHOD: Dispose of in accordance with local, state and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store in dry area. Keep away from open flames and high temperatures.

OTHER PRECAUTIONS: Minimize contact. Avoid breathing vapors. Practice good industrial hygiene and safe working practices.

SECTION 8: CONTROL MEASURES

RESPIRATORY PROTECTION: Use a NIOSH/MSHA jointly approved respirator.

VENTILATION: Use mechanical ventilation.

PROTECTIVE GLOVES: Neoprene or rubber.

EYE PROTECTION: Chemical splash goggles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Protective clothing, barrier cream, eye bath, safety shower.

SECTION 9: REGULATORY INFORMATION

D. O. T. PROPER SHIPPING NAME: Resin Solution, flammable; 3; UN1866; PG III

PROPER SHIPPING NAME: Resin Solution, flammable

HAZARD CLASS: Class 3; Flammable Liquid

UN/NA ID NUMBER: UN 1866

SECTION 10: DISCLAIMER

Data and recommendations presented herein are based upon our and other researchers and are believed to be accurate. The products discussed are distributed without warranty (expressed or implied) and the customer shall make his own determination of suitability for his particular purpose.