

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 09/05/2011

Reviewed on 04/24/2010

## 1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**

- **Trade name:** **Key# 9418 MMA SL/Trowel Resin**

- **Application of the substance / the preparation** Coating

- **Details of the supplier of the safety data sheet**

- **Manufacturer/Supplier:**

Key Resin Company  
4050 Clough Woods Drive  
OH-45103 Batavia /Ohio  
Tel.: +1 513 943-4225  
Fax.: +1 513 943-4255

- **Information department:**

Mr Eric Borglum, Tel.: +1 513 943-4225  
email: eborglum@keyresin.com











- **Emergency telephone number:** Mr. Robert Cain, Tel.: +1 513 943-4225

## 2 Composition/information on ingredients

- **Chemical characterization:** Mixtures

- **Description:** methyl methacrylate resin

- **Dangerous components:**

CAS: 80-62-6 EINECS: 201-297-1	methyl methacrylate  Xi R37/38-43;  F R11  H225;  H315; H317; H335	25-50%
CAS: 103-11-7 EINECS: 203-080-7	2-ethylhexyl acrylate  Xi R37/38-43  H315; H317; H335	10-25%
CAS: 38668-48-3 EINECS: 254-075-1	1,1'-(p-tolylimino)dipropan-2-ol  T R25;  Xi R41 R52/53  H301;  H318; H402; H412	< 2.5%

- **Additional information** For the wording of the listed risk phrases refer to section 16.

## 3 Hazards identification

- **Classification of the substance or mixture**



GHS02 Flame

H225 Highly flammable liquid and vapour.



GHS07


H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H333 May be harmful if inhaled.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**

 Xi; Irritant

R37/38-43: Irritating to respiratory system and skin. May cause sensitization by skin contact.



F; Highly flammable

R11: Highly flammable.

(Contd. on page 2)

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 09/05/2011

Reviewed on 04/24/2010

Trade name: **Key# 9418 MMA SL/Trowel Resin**

(Contd. of page 1)

· **Classification system:**

The classification was made according to the latest editions of the EU-lists, and expanded upon from company and literature data.

· **Label elements**

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials

· **Code letter and hazard designation of product:**



Xi Irritant  
F Highly flammable

· **Hazard-determining components of labelling:**

methyl methacrylate  
2-ethylhexyl acrylate

· **Risk phrases:**

11 Highly flammable.  
37/38 Irritating to respiratory system and skin.  
43 May cause sensitization by skin contact.

· **Safety phrases:**

16 Keep away from sources of ignition - No smoking.  
24 Avoid contact with skin.  
26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
28 After contact with skin, wash immediately with plenty of soap and water  
33 Take precautionary measures against static discharges.  
37 Wear suitable gloves.  
60 This material and its container must be disposed of as hazardous waste.

· **Classification system**

· **NFPA ratings (scale 0-4)**



Health = 1  
Fire = 3  
Reactivity = 0

## 4 First aid measures

- **General information** Immediately remove any clothing soiled by the product.
- **After inhalation**  
Take affected persons into fresh air and keep quiet.  
Seek medical treatment in case of complaints.
- **After skin contact**  
Immediately wash with water and soap and rinse thoroughly.  
If skin irritation continues, consult a doctor.
- **After eye contact** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing** Seek immediate medical advice.
- **Information for doctor** No particular measures are known - treat according to symptoms.

## 5 Firefighting measures

- **Suitable extinguishing agents** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents** Water.
- **Special hazards arising from the substance or mixture**  
Formation of toxic gases is possible during heating or in case of fire.

(Contd. on page 3)

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 09/05/2011

Reviewed on 04/24/2010

**Trade name: Key# 9418 MMA SL/Trowel Resin**

(Contd. of page 2)

- **Protective equipment:** Do not inhale explosion gases or combustion gases.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation
- **Environmental precautions:** Prevent seepage into sewage system, workpits and cellars.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## 7 Handling and storage

- **Handling**
- **Precautions for safe handling**  
Keep receptacles tightly sealed.  
Store in cool, dry place in tightly closed receptacles.  
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Fumes can combine with air to form an explosive mixture.  
Flammable gas-air mixtures may be formed in empty receptacles.
- **Storage**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Keep containers securely closed and dry, store at 5 - 25°C.  
Store only in the original receptacle.  
Provide floor trough without outlet.
- **Information about storage in one common storage facility:** Store away from oxidizing agents.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.  
Store only outside or in explosion proof rooms.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Components with limit values that require monitoring at the workplace:**

**80-62-6 methyl methacrylate (25-50%)**

PEL	410 mg/m <sup>3</sup> , 100 ppm
REL	410 mg/m <sup>3</sup> , 100 ppm
TLV	Short-term value: 410 mg/m <sup>3</sup> , 100 ppm Long-term value: 205 mg/m <sup>3</sup> , 50 ppm
SEN	

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Personal protective equipment**
- **General protective and hygienic measures**  
Keep away from foodstuffs, beverages and feed.  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.

(Contd. on page 4)

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 09/05/2011

Reviewed on 04/24/2010

Trade name: **Key# 9418 MMA SL/Trowel Resin**

(Contd. of page 3)

Avoid contact with the eyes and skin.

Store protective clothing separately.

Immediately remove all soiled and contaminated clothing

· **Breathing equipment:** Use suitable respiratory protective device in case of insufficient ventilation.

· **Recommended filter device for short term use:**



Filter AX

· **Protection of hands:**



Plastic gloves

Only use chemical-protective gloves with CE-labelling of category III.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Butyl rubber, BR

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.5$  mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **As protection from splashes gloves made of the following materials are suitable:** PVC gloves

· **Not suitable are gloves made of the following materials:**

Leather gloves

Strong gloves

· **Eye protection:**



Tightly sealed goggles.

· **Body protection:** Protective work clothing.

## 9 Physical and chemical properties

· **General Information**

· **Appearance:**

**Form:** Viscous

**Color:** bluish

Cloudy

· **Odor:** Ester-like

Sweetish

· **Change in condition**

**Melting point/Melting range:** undetermined

**Boiling point/Boiling range:** undetermined

· **Flash point:** 10°C (50 °F) (DIN 51755)

(Contd. on page 5)

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 09/05/2011

Reviewed on 04/24/2010

**Trade name: Key# 9418 MMA SL/Trowel Resin**

(Contd. of page 4)

· <b>Ignition temperature:</b>	245°C (473 °F)
· <b>Auto igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· <b>Explosion limits:</b>	
<b>Lower:</b>	0.8 Vol %
<b>Upper:</b>	12.5 Vol %
· <b>Vapor pressure at 25°C (77 °F):</b>	47 hPa (35 mm Hg)
· <b>Density at 20°C (68 °F):</b>	ca. 0.97 g/cm <sup>3</sup>
· <b>Solubility in / Miscibility with Water at 20°C (68 °F):</b>	max 16 g/l
· <b>Viscosity:</b>	
<b>dynamic at 23°C (73 °F):</b>	41-47 mPas (Brookfield)
<b>kinematic at 23°C (73 °F):</b>	25-30 s (DIN 53211/4)
· <b>Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Incompatible materials:**
  - acids
  - strong oxidizing agents
- **Hazardous decomposition products:**
  - in the event of fire:
  - toxic gases and vapours
  - Flammable gases/vapors

## 11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

### 80-62-6 methyl methacrylate

Oral	LD50	> 5000 mg/kg (rat)
Dermal	LD50	> 5000 mg/kg (rab)
Inhalative	LC50/4 h	7093 mg/l (rat)

### 103-11-7 2-ethylhexyl acrylate

Oral	LD50	4435 mg/kg (rat)
Dermal	LD50	> 5000 mg/kg (rab)
Inhalative	LC50/4 h	600 mg/l (rat)

### 38668-48-3 1,1'-(p-tolylimino)dipropan-2-ol

Oral	LD50	100 mg/kg (rat)
------	------	-----------------

- **Primary irritant effect:**
  - **on the skin:** Irritant to skin and mucous membranes.
  - **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

(Contd. on page 6)

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 09/05/2011

Reviewed on 04/24/2010

**Trade name: Key# 9418 MMA SL/Trowel Resin**

Irritant

(Contd. of page 5)

## 12 Ecological information

### · Aquatic toxicity:

#### 80-62-6 methyl methacrylate

BSB5-Wert	0.14 g/g (-)
EC0	100 mg/l ( <i>Pseudomonas putida</i> )
EC3	(192h) 37 mg/l ( <i>Scenedesmus quadricauda</i> )
EC50	(96h) 170 mg/l ( <i>Selenastrum capricornutum</i> ) (48h) 69 mg/l ( <i>daphnia</i> )
LC50	350 mg/l ( <i>Leuciscus idus</i> )
LC50 (96h)	>79 mg/l ( <i>Onchorhynchus mykiss</i> ) 232 mg/l ( <i>Lepomis macrochirus (bluegill)</i> ) 277 mg/l ( <i>Carassius auratus (Goldfisch)</i> )

#### 103-11-7 2-ethylhexyl acrylate

EC0	(192h) 0.06 mg/l ( <i>Microcystis aeruginosa</i> )
EC50	(48h) 17.5 mg/l ( <i>daphnia</i> ) (0.5h) > 1000 mg/l ( <i>Pseudomonas putida</i> )
EC50 (72h)	44 mg/l ( <i>Scenedesmus subspicatus</i> )
LC50	(48h) 23 mg/l ( <i>Leuciscus idus</i> )

#### 38668-48-3 1,1'-(p-tolylimino)dipropan-2-ol

BSB-5	11 mg O2/g (-)
CSB	2360 mg O2/g (-)
EC50	(48h) 28.8 mg/l ( <i>Daphnia magna</i> )

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Ecotoxicological effects:** Not determined

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

## 13 Disposal considerations

· **Waste treatment methods**

· **Recommendation** Must be specially treated adhering to official regulations.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

· **UN-Number**

· **DOT** UN1866

· **ADR, IMDG, IATA** 1866

· **UN proper shipping name**

· **DOT, IMDG, IATA** RESIN SOLUTION

(Contd. on page 7)

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 09/05/2011

Reviewed on 04/24/2010

**Trade name: Key# 9418 MMA SL/Trowel Resin**

(Contd. of page 6)

· **ADR** 1866 RESIN SOLUTION

· **Transport hazard class(es)**

· **DOT, IMDG, IATA**



· **Class** 3 Flammable liquids.

· **Label** 3

· **ADR**



· **Class** 3 (F1) Flammable liquids

· **Label** 3

· **Packing group**

· **DOT, ADR, IMDG, IATA** II

· **Environmental hazards:**

· **Marine pollutant:** No

· **Special precautions for user** Warning: Flammable liquids

· **Danger code (Kemler):** 33

· **EMS Number:** F-E,S-E

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **UN "Model Regulation":** UN1866, RESIN SOLUTION, 3, II

## 15 Regulatory information

· **Carcinogenity categories**

· **EPA (Environmental Protection Agency)**

80-62-6	methyl methacrylate	E;NL
---------	---------------------	------

· **IARC (International Agency for Research on Cancer)**

80-62-6	methyl methacrylate	3
103-11-7	2-ethylhexyl acrylate	3
128-37-0	2,6-di-tert-butyl-p-cresol	3

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

80-62-6	methyl methacrylate	A4
128-37-0	2,6-di-tert-butyl-p-cresol	A4

· **MAK (German Maximum Workplace Concentration)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

(Contd. on page 8)

**Material Safety Data Sheet**  
acc. to ISO/DIS 11014

Printing date 09/05/2011

Reviewed on 04/24/2010

**Trade name: Key# 9418 MMA SL/Trowel Resin**

(Contd. of page 7)

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

· **Markings according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials

· **Code letter and hazard designation of product:**



Xi Irritant  
F Highly flammable

· **Hazard-determining components of labelling:**

methyl methacrylate  
2-ethylhexyl acrylate

· **Risk phrases:**

11 Highly flammable.  
37/38 Irritating to respiratory system and skin.  
43 May cause sensitization by skin contact.

· **Safety phrases:**

16 Keep away from sources of ignition - No smoking.  
24 Avoid contact with skin.  
26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
28 After contact with skin, wash immediately with plenty of soap and water  
33 Take precautionary measures against static discharges.  
37 Wear suitable gloves.  
60 This material and its container must be disposed of as hazardous waste.

· **National regulations**

· **Technical instructions (air):**

· **VOC USA % 0.1 g/l / 0.00 lb/gl**

· **Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.**

· **Sara**

· **Section 355 (Extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

80-62-6 | methyl methacrylate

· **TSCA (Toxic Substances Control Act):**

80-62-6	methyl methacrylate
103-11-7	2-ethylhexyl acrylate
2082-81-7	1,4-Butandioldimethacrylat
23077-12-1	??
31570-04-4	Tris(2,4-di-tert-butylphenyl)phosphit
2440-22-4	2-(2H-Benotriazol-2-yl)-p-kresol

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 9)

**Material Safety Data Sheet**  
acc. to ISO/DIS 11014

Printing date 09/05/2011

Reviewed on 04/24/2010

**Trade name: Key# 9418 MMA SL/Trowel Resin**

(Contd. of page 8)

· **Relevant phrases**

- H225 Highly flammable liquid and vapour.  
 H301 Toxic if swallowed.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H335 May cause respiratory irritation.  
 H402 Harmful to aquatic life.  
 H412 Harmful to aquatic life with long lasting effects.
- R11 Highly flammable.  
 R25 Toxic if swallowed.  
 R37/38 Irritating to respiratory system and skin.  
 R41 Risk of serious damage to eyes.  
 R43 May cause sensitization by skin contact.  
 R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment

· **Department issuing MSDS:**

IGG-AD Ingenieurbüro für Gefahrstoff- und Gefahrgutberatung  
 Bismarckstraße 10  
 D-68623 Lampertheim  
 Fax: 0049-(0)6206-58422      <http://www.igg-ad.de>      [info@igg-ad.de](mailto:info@igg-ad.de)

· **Contact:**

Dr. U. Prinz ([u.prinz@igg-ad.de](mailto:u.prinz@igg-ad.de))  
 Dipl.-Chem. H. Hinse ([heidrun.hinse@igg-ad.de](mailto:heidrun.hinse@igg-ad.de))

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 ICAO: International Civil Aviation Organization  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 NFPA: National Fire Protection Association (USA)  
 MAL-Code: Måleteknisk Arbejdshygiejnisk Lufibehov (Regulation for the labeling concerning inhalation hazards, Denmark)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent

· **\* Data compared to the previous version altered.**

USA