

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 09/05/2011

Reviewed on 04/24/2010

1 Identification of the substance/mixture and of the company/undertaking

· **Product identifier**

· **Trade name:** **Key# 9430 MMA Joint Filler Resin**

· **Application of the substance / the preparation** Coating

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Key Resin Company
4050 Clough Woods Drive
OH-45103 Batavia /Ohio
Tel.: +1 513 943-4225
Fax.: +1 513 943-4255

· **Information department:**

Mr Eric Borglum, Tel.: +1 513 943-4225
email: eborglum@keyresin.com

· **Emergency telephone number:** Mr. Robert Cain, Tel.: +1 513 943-4225

2 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** methyl methacrylate resin

· **Dangerous components:**

CAS: 103-11-7 EINECS: 203-080-7	2-ethylhexyl acrylate Xi R37/38-43 H315; H317; H335	10-25%
CAS: 80-62-6 EINECS: 201-297-1	methyl methacrylate Xi R37/38-43; F R11 H225; H315; H317; H335	10-25%
CAS: 105-76-0 EINECS: 203-328-4	dibutyl maleate Xn R22-48; Xi R43 H301; H317; H313	10-25%
CAS: 97-88-1 EINECS: 202-615-1	butyl methacrylate Xi R36/37/38-43 R10 H226; H315; H319; H317; H335	2.5-10%
CAS: 38668-48-3 EINECS: 254-075-1	1,1'-(p-tolylimino)dipropan-2-ol T R25; Xi R41 R52/53 H301; H318; H402; H412	< 2.5%

· **Additional information** For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

· **Classification of the substance or mixture**



GHS02 Flame

H225 Highly flammable liquid and vapour.



GHS08 Health hazard

H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

(Contd. on page 2)

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 09/05/2011

Reviewed on 04/24/2010

Trade name: Key# 9430 MMA Joint Filler Resin

(Contd. of page 1)

- H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.
 H335 May cause respiratory irritation.
 H303 May be harmful if swallowed.
 H333 May be harmful if inhaled.

· **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Xi; Irritant

R37/38-43: Irritating to respiratory system and skin. May cause sensitization by skin contact.



F; Highly flammable

R11: Highly flammable.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· **Label elements**

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials

· **Code letter and hazard designation of product:**



Xi Irritant

F Highly flammable

· **Hazard-determining components of labelling:**

2-ethylhexyl acrylate
 methyl methacrylate
 dibutyl maleate
 butyl methacrylate

· **Risk phrases:**

- 11 Highly flammable.
 37/38 Irritating to respiratory system and skin.
 43 May cause sensitization by skin contact.
 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment

· **Safety phrases:**

- 9 Keep container in a well-ventilated place.
 16 Keep away from sources of ignition - No smoking.
 24/25 Avoid contact with skin and eyes.
 33 Take precautionary measures against static discharges.
 37 Wear suitable gloves.
 60 This material and its container must be disposed of as hazardous waste.
 61 Avoid release to the environment. Refer to special instructions/Safety data sheets

(Contd. on page 3)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 09/05/2011

Reviewed on 04/24/2010

Trade name: **Key# 9430 MMA Joint Filler Resin**

(Contd. of page 2)

- **Classification system**
- **NFPA ratings (scale 0-4)**



Health = 1
Fire = 3
Reactivity = 0

4 First aid measures

- **General information**

Immediately remove any clothing soiled by the product.
Take affected persons out into the fresh air.

- **After inhalation**

Take affected persons into fresh air and keep quiet.
Seek medical treatment in case of complaints.

- **After skin contact**

Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.

- **After eye contact** Rinse opened eye for several minutes under running water. Then consult a doctor.

- **After swallowing** Seek immediate medical advice.

- **Information for doctor** No particular measures are known - treat according to symptoms.

5 Firefighting measures

- **Suitable extinguishing agents** CO₂, sand, extinguishing powder. Do not use water.

- **For safety reasons unsuitable extinguishing agents** Water with full jet.

- **Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

- **Protective equipment:** Do not inhale explosion gases or combustion gases.

- **Additional information**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

Keep away from ignition sources

Wear protective clothing.

- **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Do not allow to penetrate the ground/soil.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

- **Reference to other sections**

Clean the accident area carefully.

See Section 8 for information on personal protection equipment.

7 Handling and storage

- **Handling**

- **Precautions for safe handling**

Keep receptacles tightly sealed.

Store in cool, dry place in tightly closed receptacles.

(Contd. on page 4)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 09/05/2011

Reviewed on 04/24/2010

Trade name: **Key# 9430 MMA Joint Filler Resin**

(Contd. of page 3)

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Fumes can combine with air to form an explosive mixture.

Flammable gas-air mixtures may be formed in empty receptacles.

· **Storage**

· **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Keep containers securely closed and dry, store at 5 - 25°C.

Store only in the original receptacle.

Provide floor trough without outlet.

· **Information about storage in one common storage facility:** Store away from oxidizing agents.

· **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Store only outside or in explosion proof rooms.

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Components with limit values that require monitoring at the workplace:**

80-62-6 methyl methacrylate (10-25%)

PEL 410 mg/m³, 100 ppm

REL 410 mg/m³, 100 ppm

TLV Short-term value: 410 mg/m³, 100 ppm

Long-term value: 205 mg/m³, 50 ppm

SEN

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Personal protective equipment**

· **General protective and hygienic measures**

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Immediately remove all soiled and contaminated clothing

Store protective clothing separately.

· **Breathing equipment:** Use suitable respiratory protective device in case of insufficient ventilation.

· **Recommended filter device for short term use:**



Combination filter A-P2

· **Protection of hands:**



Only use chemical-protective gloves with CE-labelling of category III.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Nitrile rubber, NBR

Butyl rubber, BR

(Contd. on page 5)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 09/05/2011

Reviewed on 04/24/2010

Trade name: **Key# 9430 MMA Joint Filler Resin**

(Contd. of page 4)

Recommended thickness of the material: ≥ 0.5 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Not suitable are gloves made of the following materials:**

Leather gloves

Strong gloves

· **Eye protection:**



Goggles recommended during refilling.

· **Body protection:** Protective work clothing.

9 Physical and chemical properties

· **General Information**

· **Appearance:**

Form: Fluid
Color: Yellowish
 Transparent

· **Odor:** Ester-like

· **Change in condition**

Melting point/Melting range: undetermined

Boiling point/Boiling range: undetermined

· **Flash point:** $< 21^{\circ}\text{C}$ ($< 70^{\circ}\text{F}$)

· **Ignition temperature:** 245°C (473°F)

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

Lower: 0.8 Vol %

Upper: 12.5 Vol %

· **Vapor pressure at 25°C (77°F):** 47 hPa (35 mm Hg)

· **Density:** Not determined

· **Solubility in / Miscibility with**

Water: Partly miscible

· **Organic solvents:** Soluble in many organic solvents

· **Other information** No further relevant information available.

10 Stability and reactivity

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **Incompatible materials:**

acids

strong oxidizing agents

(Contd. on page 6)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 09/05/2011

Reviewed on 04/24/2010

Trade name: Key# 9430 MMA Joint Filler Resin

(Contd. of page 5)

- **Hazardous decomposition products:**
in the event of fire:
toxic gases and vapours
Flammable gases/vapours

11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

103-11-7 2-ethylhexyl acrylate

Oral	LD50	4435 mg/kg (rat)
Dermal	LD50	> 5000 mg/kg (rab)
Inhalative	LC50/4 h	600 mg/l (rat)

80-62-6 methyl methacrylate

Oral	LD50	> 5000 mg/kg (rat)
Dermal	LD50	> 5000 mg/kg (rab)
Inhalative	LC50/4 h	7093 mg/l (rat)

105-76-0 dibutyl maleate

Oral	LD50	3730 mg/kg (rat)
Dermal	LD50	10000 mg/kg (rbt)

97-88-1 butyl methacrylate

Oral	LD50	22600 mg/kg (rat)
Dermal	LD50	11300 mg/kg (rbt)
Inhalative	LC50/4 h	4910 mg/l (rat)

38668-48-3 1,1'-(p-tolylimino)dipropan-2-ol

Oral	LD50	100 mg/kg (rat)
------	------	-----------------

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant

12 Ecological information

- **Aquatic toxicity:**

103-11-7 2-ethylhexyl acrylate

EC0	(192h) 0.06 mg/l (Microcystis aeruginosa)
EC50	(48h) 17.5 mg/l (daphnia)
	(0.5h) > 1000 mg/l (Pseudomonas putida)
EC50 (72h)	44 mg/l (Scenedesmus subspicatus)
LC50	(48h) 23 mg/l (Leuciscus idus)

80-62-6 methyl methacrylate

BSB5-Wert	0.14 g/g (-)
EC0	100 mg/l (Pseudomonas putida)
EC3	(192h) 37 mg/l (Scenedesmus quadicauda)
EC50	(96h) 170 mg/l (Selenastrum capricornutum)

(Contd. on page 7)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 09/05/2011

Reviewed on 04/24/2010

Trade name: Key# 9430 MMA Joint Filler Resin

(Contd. of page 6)

LC50	(48h) 69 mg/l (daphnia) 350 mg/l (Leuciscus idus)
LC50 (96h)	>79 mg/l (Onchorhynchus mykiss) 232 mg/l (Lepomis macrochirus (bluegill)) 277 mg/l (Carassius auratus (Goldfish))
105-76-0 dibutyl maleate	
EC0	ca. 40 mg/l (bacteria)
EC0 (48h)	10 mg/l (Daphnia magna)
EC100	(48h) 32 mg/l (Daphnia magna)
EC50	(48h) 21 mg/l (Daphnia magna)
EC50 (72h)	6.2 mg/l (Scenedesmus subspicatus)
LC0	(48h) ca. 12 mg/l (Leuciscus idus)
LC50 (96h)	1.2 mg/l (Salmo gairdneri)
NOEC	(72h) 4.2 mg/l (Scenedesmus subspicatus)
97-88-1 butyl methacrylate	
EC50	(48h) 25.4 mg/l (Daphnia magna) (18h) > 253.6 mg/l (Pseudomonas putida)
EC50 (72h)	31.2 mg/l (Selenastrum capricornutum)
LC50 (96h)	5.57 mg/l (Orycias Latipes)
NOEC	(14d) 0.8 mg/l (Orycias Latipes) (21d) 1.1 mg/l (Daphnia magna)
38668-48-3 1,1'-(p-tolylimino)dipropan-2-ol	
BSB-5	11 mg O ₂ /g (-)
CSB	2360 mg O ₂ /g (-)
EC50	(48h) 28.8 mg/l (Daphnia magna)

- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Ecotoxicological effects:** Not determined
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Harmful to aquatic organisms

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation** Must be specially treated adhering to official regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT** UN1866

(Contd. on page 8)



Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 09/05/2011

Reviewed on 04/24/2010

Trade name: Key# 9430 MMA Joint Filler Resin

(Contd. of page 7)

· ADR, IMDG, IATA	1866
· UN proper shipping name · DOT, IATA · ADR · IMDG	RESIN SOLUTION 1866 RESIN SOLUTION RESIN SOLUTION (METHYL METHACRYLATE MONOMER, STABILIZED)
· Transport hazard class(es) · DOT, IMDG, IATA	
	
· Class · Label	3 Flammable liquids. 3
· ADR	
	
· Class · Label	3 (F1) Flammable liquids 3
· Packing group · DOT, ADR, IMDG, IATA	II
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user · Danger code (Kemler): · EMS Number:	Warning: Flammable liquids 33 F-E,S-E
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	UN1866, RESIN SOLUTION, 3, II

15 Regulatory information

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

80-62-6	methyl methacrylate	E;NL
---------	---------------------	------

· **IARC (International Agency for Research on Cancer)**

80-62-6	methyl methacrylate	3
103-11-7	2-ethylhexyl acrylate	3
128-37-0	2,6-di-tert-butyl-p-cresol	3

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

80-62-6	methyl methacrylate	A4
128-37-0	2,6-di-tert-butyl-p-cresol	A4

(Contd. on page 9)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 09/05/2011

Reviewed on 04/24/2010

Trade name: Key# 9430 MMA Joint Filler Resin

(Contd. of page 8)

· **MAK (German Maximum Workplace Concentration)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

· **Markings according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials

· **Code letter and hazard designation of product:**



Xi Irritant
F Highly flammable

· **Hazard-determining components of labelling:**

2-ethylhexyl acrylate
methyl methacrylate
dibutyl maleate
butyl methacrylate

· **Risk phrases:**

11 Highly flammable.
37/38 Irritating to respiratory system and skin.
43 May cause sensitization by skin contact.
52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment

· **Safety phrases:**

9 Keep container in a well-ventilated place.
16 Keep away from sources of ignition - No smoking.
24/25 Avoid contact with skin and eyes.
33 Take precautionary measures against static discharges.
37 Wear suitable gloves.
60 This material and its container must be disposed of as hazardous waste.
61 Avoid release to the environment. Refer to special instructions/Safety data sheets

· **National regulations**

· **Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
· **Sara**

· **Section 355 (Extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

80-62-6 methyl methacrylate

· **TSCA (Toxic Substances Control Act):**

80-62-6	methyl methacrylate
103-11-7	2-ethylhexyl acrylate
103-83-3	benzyl dimethylamine
3077-12-1	2,2'-[(4-methylphenyl)imino]bisethanol
2082-81-7	1,4-Butandiol dimethacrylat

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

USA

(Contd. on page 10)

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 09/05/2011

Reviewed on 04/24/2010

Trade name: Key# 9430 MMA Joint Filler Resin

(Contd. of page 9)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H225 *Highly flammable liquid and vapour.*
- H226 *Flammable liquid and vapour.*
- H301 *Toxic if swallowed.*
- H313 *May be harmful in contact with skin.*
- H315 *Causes skin irritation.*
- H317 *May cause an allergic skin reaction.*
- H318 *Causes serious eye damage.*
- H319 *Causes serious eye irritation.*
- H335 *May cause respiratory irritation.*
- H402 *Harmful to aquatic life.*
- H412 *Harmful to aquatic life with long lasting effects.*
- R10 *Flammable.*
- R11 *Highly flammable.*
- R22 *Harmful if swallowed.*
- R25 *Toxic if swallowed.*
- R36/37/38 *Irritating to eyes, respiratory system and skin.*
- R37/38 *Irritating to respiratory system and skin.*
- R41 *Risk of serious damage to eyes.*
- R43 *May cause sensitization by skin contact.*
- R48 *Danger of serious damage to health by prolonged exposure.*
- R52/53 *Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment*

· **Department issuing MSDS:**

IGG-AD Ingenieurbüro für Gefahrstoff- und Gefahrgutberatung
Bismarckstraße 10
D-68623 Lampertheim
Fax: 0049-(0)6206-58422 <http://www.igg-ad.de> info@igg-ad.de

· **Contact:**

Dr. U. Prinz (u.prinz@igg-ad.de)
Dipl.-Chem. H. Hinse (heidrun.hinse@igg-ad.de)

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
ICAO: International Civil Aviation Organization
ACGIH: American Conference of Governmental Industrial Hygienists
NFPA: National Fire Protection Association (USA)
MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent

· *** Data compared to the previous version altered.**